

dynaGlide Plus® will increase your production.

Less time sharpening, cleaning, and maintaining tools and equipment.

Available in dynaGlide Plus w/HD 4X and the Original dynaGlide Wood & Tool Conditioner





Cleans and prevents router bearing heat build-up to extend bearing life.



Extends sharp cutting life of all Bits and Shapers.



Removes and prevents build-up on abrasives.



Cleans and prevents resin and glue build-up.

Use on Woodworking & **Metalworking Tools, Use on any Metals**

dynaGLIDE® will not stain, discolor, or transfer. dynaGLIDE® penetrates instantly and dries within minutes, leaving behind extremely tough pressure film.

Can be used for storage of tools, all router bearings, table beds, scrollsaw, ban-saw, cutters, lathe tools, all cutting/drilling/routing blades, etc. Will not stain wood or other material.

> Replaces all other lubricants for any purpose.

Silicone and Teflon FREE

Visit us at: www.dynaglideplus.com/tool

Tri-Boundary Dry-Lubricant

- * 3.300+lb (Falex test) Load Carry capacity
- Reduces Friction/Heat 2 times(+) over conventional lubes
- 3 times better Cutting Performance of all Blades, Bits, Abrasives, and Equipment
- Displaces moisture, rust, grit, gunk
- HD4X™ Blocks Rust, Tarnish and Oxide Corrosion

Extends All Cutting/Drilling/Routing & Tool Life

- Minimizes Sharpening/Cleaning Cycles, Keeps tools sharp 2 times(+) longer
- · Retards Resin/Glue Build-up

Table Top Cleaner/Conditioner

- Non-Gumming "Table Top" Coating no gummy build-up
- Cleans & Conditions All Metal surfaces
- Eliminates Drag
- Displaces & Cleans Grit, Grime, Old Oils & Greases
- Passes 400 hour Salt Spray test Humidity & Water will not remove HD4X™



Ergonomic Comfort

Grip Design





NON-MIGRATING DRY-FILM ELIMINATES FISH EYE PROBLEMS

Available in dynaGlide Plus with HD 4X for Tool & Surface and the Original dynaGlide Wood & Tool Conditioner





Scan QR Code
For more technical
information and MSDS
Safety Data information.
Use smart phone.

Manufactured by:

Multi-Marketing Corporation Tacoma, WA 98446 1-800-825-9256 www.dynaGlideplus.com

dynaGlide Plus® with **HD4X™**A dry-film Lubricant, Cleaner & Conditioner for TOOLS, SURFACES and ALL METALS

Expressly formulated & compounded to extend the life of tools, machine parts & equipment.

PRECISE SPRAY COMFORT GRIP Adjustable Flow tube extension spray or fine fan spray dynaGlide Plus™ Comfort Trigger Sprayer provides a wide continuous spray pattern for large surface area applications as well as a fine precision spray when using the tube extension.

dynaGlide® and dynaGlide Plus® are Dual & Tri-Boundary dry lubricants with unique proprietary additives engineered for all tools and metal surfaces. HD4X™ is a proprietary rust and corrosion preventive that blocks oxidation on all metals...

dynaGlide Plus[®] with HD4X[™] protects in extreme conditions of pressure, heat and moisture...

- Creates a dry-film boundary that carries a 3,300 lbs load carrying capacity (six times US military spec)
- Will protect all metals from warping or overheating up to 450 degrees
- Water and humidity will not diminish the effectiveness of the HD4XTM film
- Cleans and prevents router bearing heat build-up to extend bearing life
- Extends sharp cutting life of all saws, bits, routers and shapers
- Cleans and prevents resin and glue build-up on any metal, plastic, rubber surfaces and abrasives
- · Eliminates drag and build-up on table beds & saws blades
- Use on woodworking and metal tools, safe for use on any metal – will not harm wood
- Prevents rust and corrosion from forming on metals (400 to 600 hours in salt spray test)

Best results are achieved with two initial cleanings of metal surfaces with dynaGlide® formula before the first conditioned application use. Thereafter one cleaning/conditioning application of dynaGlide® formula renews the metal surface for continued use.

Distributed by: MICRO FENCE



microfence@microfence.com www.microfence.com Micro Fence® Richard Wedler 12970 Branford St. Unit M Arleta, CA 91331

Phone: 818.683.0330 Fax: 818.683.0374 Orders: 800.480.6427